

# ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A1

Owner of the Declaration	dormakaba International Holding GmbH
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DOR-20200114-CBD4-EN
Issue date	01.07.2021
Valid to	30.06.2026

**BEST HD7000**  
**dormakaba**

[www.ibu-epd.com](http://www.ibu-epd.com) | <https://epd-online.com>



## General Information

### dormakaba

#### Programme holder

IBU – Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

#### Declaration number

EPD-DOR-20200114-CBD4-EN

#### This declaration is based on the product category rules:

Building Hardware products, 01.08.2021  
(PCR checked and approved by the SVR)

#### Issue date

01.07.2021

#### Valid to

30.06.2026



Dipl.-Ing. Hans Peters  
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold  
(Managing Director Institut Bauen und Umwelt e.V.)

### BEST HD7000

#### Owner of the declaration

dormakaba International Holding GmbH  
DORMA Platz 1  
58256 Ennepetal  
Germany

#### Declared product / declared unit

The declaration represents one surface applied door closer unit.

#### Scope:

The declaration and the background LCA represent dormakaba's BEST HD7000 Series door closers. Raw materials are provided by suppliers, but the closers are manufactured and assembled at dormakaba facilities worldwide. Closer bodies are manufactured at dormakaba's Singapore facility and components of the closer arm are manufactured at dormakaba facilities in Ennepetal, Germany and Reamstown, USA. These parts are then shipped to Indianapolis, USA, where the final assembly takes place. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A1. In the following, the standard will be simplified as *EN 15804*.

#### Verification

The standard EN 15804 serves as the core PCR		
Independent verification of the declaration and data according to ISO 14025:2011		
<input type="checkbox"/>	internally	<input checked="" type="checkbox"/> externally



Dr.-Ing. Wolfram Trinius,  
(Independent verifier)

## Product

### Product description/Product definition

The HD7000 Series door closers are non-handed surface applied door closers with adjustable spring power (size 1-6) and backcheck that controls opening motion during abusive or abrupt opening.

Supported by a full complement of optional arms, plates, and brackets, the door closers provide the flexibility needed to meet the demands of commercial and institutional applications, including Americans with Disabilities Act (ADA) barrier-free accessibility requirements.

The door closers are available with slim plastic, full plastic and full metal cover. For the use and application of the product the respective national provisions at the place of use apply. The standards which can be applied are the following:

- ANSI/BHMA 156.4
- ANSI/ICC A117.1
- UL listed product
- UL 10C
- ADA compliant (version 1-6)

### Application

The HD7000 Series door closers are designed for commercial and institutional applications, including ADA barrier-free accessibility requirements.

They are suitable for use on hollow metal, aluminum and wood doors and can be used for fire doors.

### Technical Data

The HD7000 Series have two independent adjustment valves to control the closing speed from 180° - 10° and from 10° - 0°. Optional delayed action adjustable with a separate independent valve delays door closing to allow unobstructed passage through the opening.

Based on arm selection, the mounting options are regular (pull side of the door), top jamb (push side of the door) and parallel arm (push side of the door).

Performance data of the product with respect to its characteristics in accordance with the relevant technical

provision which can be applied include product certifications like ANSI A156.4 Grade 1, UL 10C, and ANSI A117.1. The closers are also Underwriters Laboratories (label for the US, UL) and Label for Canada (CUL) listed, and CSFM (California State Fire Marshall) approved. The plants in Singapore, Ennepetal, Reamstown and Indianapolis are certified to the quality management system ISO 9001, which ensures consistent quality of dormakaba's products.

The Environmental Management System in the Singapore, Ennepetal, Reamstown and Indianapolis production is certified to ISO 14001. The production in Singapore and Ennepetal are also certified to the Energy Management System ISO 50001.

### Base materials/Ancillary materials

Name	Value	Unit
Steel	62	%
Aluminum	24	%
Oil	6	%
Plastics	5	%
Coatings	2	%
Other	1	%

The products include partial articles which contain substances listed in

the Candidate List of REACH Regulation 1907/2006/EC (date: 15.01.2019) exceeding 0.1 percentage by mass in the alloy:

- Lead (Pb): 7439-290-1 (CAS-No.)

The Candidate List can be found on the ECHA website address: <https://echa.europa.eu/de/home>.

### Reference service life

The reference service life of dormakaba's HD7000 Series door closers depends on the traffic pattern and degree of usage of the door. These closers are rated to ANSI Grade 1, meaning they are designed to withstand a minimum of 1,500,000 cycles. The reference service life amounts for 20 years.

## LCA: Calculation rules

### Declared Unit

The declared unit of this analysis is one surface applied door closer.

Name	Value	Unit
Declared unit (1 closer)	1	piece/product
Mass of system (without packaging)	3.0	kg

### System boundary

Type of EPD: cradle to gate - with options.

The Environmental Product Declaration refers to the production stage (A1-A3), transport from the gate to construction site (A4), the end of life stage (C3) and indicates the recycling potential which is declared in the module "benefits and loads beyond the product system boundary" (D).

In line with the PCR, A5 is declared to ensure the export of biogenic CO2 from renewable packaging materials.

Modules A1 to A3 include the provision and processing of raw materials as well as the processing of input materials, the transport to manufacturer and production site. Module C3

includes the incineration of plastics for energy recovery. Module D comprises the recycling of metals and gives the recycling potentials as well as potential benefits from energy substitution.

A5 is declared to ensure the export of biogenic CO2 that is incorporated in the used packaging materials (paper). Potential benefits from the incineration of packaging materials are also declared in module D. The incineration processes in the End-of-Life are based on European datasets. The recycling processes in the End-of-Life are based on mainly European datasets.

### Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Unbekannt

### Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to EN 15804 and the building context, respectively the product-specific characteristics of performance, are taken into account.

## LCA: Scenarios and additional technical information

Additional technical information for the declared modules.

### Transport to the building site (A4)

Name	Value	Unit
Litres of fuel truck (per piece)	0.006	l/100km
Transport distance average (ship)	13000	km
Transport distance average (truck)	1900	km
Transport distance range (truck)	10 - 4600	km
Transport distance range (ship)	0 - 21900	km
Capacity utilisation (including empty runs)	85	%

In order to represent dormakaba's global distribution network, a sales-weighted average is used to model transport to the building site. The table for Module A4 shows both weighted average transportation distance (given regional surface closer sales), which is used in the analysis.

### Installation into the building (A5)

Name	Value	Unit
Output substances following waste treatment on site (packaging)	0.257	kg

### End of life (C1-C4)

Name	Value	Unit
Recycling	3	kg

### Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Recycling	100	%

Collection rate is 100%.

## LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	MND	MND	MND	MND	X	MND	X

### RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A1: 1 closer (3.0kg)

Parameter	Unit	A1-A3	A4	A5	C3	D
Global warming potential (GWP)	kg CO <sub>2</sub> eq	2.47E+01	8.31E-01	1.06E-01	6.24E-01	-1E+01
Depletion potential of the stratospheric ozone layer (ODP)	kg CFC11 eq	1.13E-12	6.74E-17	2.56E-17	3.58E-16	1.03E-13
Acidification potential of land and water (AP)	kg SO <sub>2</sub> eq	1.03E-01	1.79E-02	2.22E-05	1.48E-04	-3.82E-02
Eutrophication potential (EP)	kg PO <sub>4</sub> <sup>3</sup> eq	7.62E-03	2.05E-03	4.19E-06	1.7E-05	-2.53E-03
Formation potential of tropospheric ozone photochemical oxidants (POCP)	kg Ethen eq	9.56E-03	4.48E-04	1.47E-06	7.07E-06	-2.82E-03
Abiotic depletion potential for non fossil resources (ADPE)	kg Sb eq	8.58E-05	2.76E-08	2.09E-09	6.01E-08	-2.5E-05
Abiotic depletion potential for fossil resources (ADPF)	MJ	2.72E+02	1.09E+01	2.95E-02	2.73E-01	-9.67E+01

### RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A1: 1 closer (3.0kg)

Parameter	Unit	A1-A3	A4	A5	C3	D
Renewable primary energy as energy carrier (PERE)	MJ	9.45E+00	4.14E-02	4.46E+00	6.55E-02	-2.94E+01
Renewable primary energy resources as material utilization (PERM)	MJ	4.46E+00	0	-4.46E+00	0	0
Total use of renewable primary energy resources (PERT)	MJ	1.39E+01	4.14E-02	5.9E-03	6.55E-02	-2.94E+01
Non renewable primary energy as energy carrier (PENRE)	MJ	2.74E+02	1.09E+01	3.45E-02	2.08E-01	-1.07E+02
Non renewable primary energy as material utilization (PENRM)	MJ	9.9E-02	0	0	9.9E-02	0
Total use of non renewable primary energy resources (PENRT)	MJ	2.74E+02	1.09E+01	3.45E-02	3.07E-01	-1.07E+02
Use of secondary material (SM)	kg	2.54E-01	0	0	0	0
Use of renewable secondary fuels (RSF)	MJ	0	0	0	0	0
Use of non renewable secondary fuels (NRSF)	MJ	0	0	0	0	0
Use of net fresh water (FW)	m <sup>3</sup>	9.54E-02	1.89E-04	3.1E-04	1.88E-03	-9E-02

### RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A1: 1 closer (3.0kg)

Parameter	Unit	A1-A3	A4	A5	C3	D
Hazardous waste disposed (HWD)	kg	8.88E-06	1.42E-09	6.66E-11	1.99E-09	-1.16E-07
Non hazardous waste disposed (NHWD)	kg	3.1E+00	8.42E-05	3.33E-03	6.43E-02	-1.64E+00
Radioactive waste disposed (RWD)	kg	8.32E-04	3.87E-06	2E-06	1.35E-05	-4.15E-03
Components for re-use (CRU)	kg	0	0	0	0	0
Materials for recycling (MFR)	kg	0	0	0	2.95E+00	0
Materials for energy recovery (MER)	kg	0	0	0	0	0
Exported electrical energy (EEE)	MJ	0	0	1.61E-01	1.2E+00	0
Exported thermal energy (EET)	MJ	0	0	2.92E-01	2.31E+00	0

Disclaimer 1 – for the indicator 'Potential Human exposure efficiency relative to U235'. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators 'abiotic depletion potential for non-fossil resources', 'abiotic depletion potential for fossil resources', 'water (user) deprivation potential, deprivation-weighted water consumption', 'potential comparative toxic unit for ecosystems', 'potential comparative toxic unit for humans – cancerogenic', 'Potential comparative toxic unit for humans - not cancerogenic', 'potential soil quality index'. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

## References

ADA  
Americans with Disabilities Act 1990

ANSI/ICC A117.1 - 2009, Accessible and usable buildings and facilities

ANSI/ICC A117.1

ANSI/BHMA A156.4

ANSI/BHMA A156.4 - 2013, Door controls - Closers

**Candidate List** of REACH Regulation /1907/2006/EC (date: 16.01.2020)

**CSFM**  
California State Fire Marshall

**ECHA**  
European Chemicals Agency

**EN 15804**  
EN 15804:2012-04 Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products

**GaBi ts**  
thinkstep AG, GaBi Software System and Database for Life Cycle Engineering (SP39). 1992-2019 Copyright thinkstep AG

**ISO 9001**  
Quality Management System - ISO 9001:2015

**ISO 14001**  
Environmental Management System - ISO 14001:2015

**ISO 14040**  
EN ISO 14040:2006, Environmental management - Life cycle assessment - Principles and framework

**ISO 14044**  
EN ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines

**ISO 50001**  
Energy Management System - ISO 50001:2011

**OHSAS 18001**  
Occupational Health and Safety - OHSAS 18001:2007

**PCR Part A**  
Institut Bauen und Umwelt e.V., Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report

**PCR Part B**  
PCR Guidance-Texts for Building-Related Products and Services. From the range of Environmental Product Declarations of Institute Construction and Environment e.V. (IBU). Part B: Requirements on the EPD for building hardware products

**REACH**  
Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Regulation (EC) No 1907/2006

**UL 10C**  
UL 10C, Positive pressure fire tests of door assemblies  
The literature referred to in the Environmental Product Declaration must be listed in full. Standards already fully quoted in the EPD do not need to be listed here again.  
The current version of PCR Part A and PCR Part B of the PCR document on which they are based must be referenced.



**Publisher**

Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

+49 (0)30 3087748- 0  
[info@ibu-epd.com](mailto:info@ibu-epd.com)  
[www.ibu-epd.com](http://www.ibu-epd.com)

---



**Programme holder**

Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

+49 (0)30 3087748- 0  
[info@ibu-epd.com](mailto:info@ibu-epd.com)  
[www.ibu-epd.com](http://www.ibu-epd.com)

---



**Author of the Life Cycle Assessment**

Sphera Solutions GmbH  
Hauptstraße 111- 113  
70771 Leinfelden-Echterdingen  
Germany

+49 (0)711 341817-0  
[info@sphera.com](mailto:info@sphera.com)  
[www.sphera.com](http://www.sphera.com)

---



**Owner of the Declaration**

dormakaba International Holding GmbH  
DORMA Platz 1  
58256 Ennepetal  
Germany

+49 2333 793-0  
[info.de@dormakaba.com](mailto:info.de@dormakaba.com)  
[www.dormakaba.com](http://www.dormakaba.com)