

# ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A1

Owner of the Declaration	dormakaba International Holding GmbH
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DOR-20200116-CBD4-EN
Issue date	24.08.2020
Valid to	23.08.2025

## BTS 75 V, BTS 75 R, RTS 87 Series door closers dormakaba

[www.ibu-epd.com](http://www.ibu-epd.com) | <https://epd-online.com>



## General Information

### dormakaba

#### Programme holder

IBU – Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

#### Declaration number

EPD-DOR-20200116-CBD4-EN

#### This declaration is based on the product category rules:

Building Hardware products, 01.08.2021  
(PCR checked and approved by the SVR)

#### Issue date

24.08.2020

#### Valid to

23.08.2025



Dipl.-Ing. Hans Peters  
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold  
(Managing Director Institut Bauen und Umwelt e.V.)

### BTS 75 V, BTS 75 R, RTS 87 Series door closers

#### Owner of the declaration

dormakaba International Holding GmbH  
DORMA Platz 1  
58256 Ennepetal  
Germany

#### Declared product / declared unit

The declaration represents one concealed door closer unit.

#### Scope:

The declaration and the background LCA represent dormakaba's BTS 75 V and RTS 87 Series Concealed Door Closers. Raw materials and components are provided by suppliers and shipped to dormakaba, where the closers are manufactured and assembled at the dormakaba facility in Singapore. The BTS 75 V, BTS 75 R (2-5) and RTS 87 differ in how they are mounted to the door (floor versus frame), but are otherwise identical products.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A1. In the following, the standard will be simplified as *EN 15804*.

#### Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally



Dr.-Ing. Wolfram Trinius,  
(Independent verifier)

## Product

### Product description/Product definition

dormakaba's BTS 75 V, BTS 75 R (2-5) and RTS 87 Series concealed door closers are dependable and versatile for almost any application. Their compact bodies enable them to be used in applications where larger closers would be prohibitive. They can be installed in a number of different configurations, including in standard, narrow or wide door frames, as well as with left-hand or right-hand single- or double-action mounting. The closers are designed for all types of doors and allow the necessary spring adjustments for both barrier-free and non-barrier free openings. A comprehensive selection of accessories ensures that they can be used successfully with a wide variety of door constructions and floor coverings. Product benefits include:

- *For the trade:* Reduced stock requirements because of adjustable closing force and separate, interchangeable spindles (BTS 75 V only), and slim product range offering all key functions.
- *For the installer:* Suitable for installation with left-hand or right-hand single and double action doors. Interchangeable spindles, as well as adjustable closing force, enable easy adaption to structural conditions - even when retrofitted (BTS 75 V only).
- *For the architect:* Concealed installation for maximum visual elegance. A wide range of applications allow architects a reliable and durable solution without compromising the aesthetics of an opening.
- *For the user:* A temperature-independent closing cycle and highly efficient mechanism gives maximum user convenience.

For the use and application of the product the respective national provisions at the place of use apply. The standards which can be applied are the following:

- ANSI A156.4 for Grade 1
- EN 1154

Product variants with mechanical hold-open are not suitable for use on Fire doors.

### Application

The BTS 75 V, BTS 75 R (2-5) and RTS 87 Series offer aesthetically pleasing solutions for both interior and exterior applications. The closers can be used in a variety of applications, including as closers for fire and smoke doors for the non-hold-open versions.

### Technical Data

The concealed door closers employ a cam and roller mechanism, and are capable of controlling interior or exterior doors weighing up to 120 kg. They have an adjustable closing force from EN 1 to EN 4 and a mechanical backcheck at approximately 70°. Dual valve adjustment provides a controlled closing speed from approximately 175° opening range, even in cold temperature conditions.

The Environmental Management System in the Singapore production is certified to ISO 14001 and the Energy Management to ISO 50001.

Name	Value	Unit
Length	285	mm
Width	82	mm
Height	50	mm
Weight	2.9	kg
Test standards and methods	EN 1154	

Performance data of the product with respect to its characteristics in accordance with the relevant technical provision which can be applied are mentioned above.

### Base materials/Ancillary materials

Name	Value	Unit
Steel	44	%
Aluminum	44	%
Zinc	6	%
Oil	5	%
Coatings and others	1	%

The products include partial articles which contain substances listed in the *Candidate List* of REACH Regulation 1907/2006/EC (date: 15.01.2019) exceeding 0.1 percentage by mass in the alloy:

- Lead (Pb): 7439-290-1 (CAS-No.)

The *Candidate List* can be found on the ECHA website address: <https://echa.europa.eu/de/home>.

### Reference service life

The reference service life of dormakaba's BTS 75 V, BTS 75 R, RTS 87 concealed door closers depends on the traffic pattern and degree of usage of the door. The reference service life amounts for 20 years.

## LCA: Calculation rules

### Declared Unit

The declared unit of this analysis is one concealed door closer.

Name	Value	Unit
Declared unit (1 closer)	1	piece/product
Mass of system (without packaging)	2.9	kg
Conversion factor to 1 kg	0.345	-
Mass of declared Product	2.9	kg

### System boundary

Type of EPD: cradle to gate - with options.

The Environmental Product Declaration refers to the production stage (A1-A3), transport from the gate to construction site (A4), the end of life stage (C3) and indicates the recycling

potential which is declared in the module "benefits and loads beyond the product system boundary" (D).

In line with the PCR, A5 is declared to ensure the export of biogenic CO<sub>2</sub> from renewable packaging materials.

Modules A1 to A3 include the provision and processing of raw materials as well as the processing of input materials, the transport to manufacturer and production site. Module C3 includes the incineration of plastics for energy recovery. Module D comprises the recycling of metals and gives the recycling potentials as well as potential benefits from energy substitution.

A5 is declared to ensure the export of biogenic CO<sub>2</sub> that is incorporated in the used packaging materials (paper). Potential benefits from the incineration of packaging materials are also

declared in module D. The incineration processes in the End-of-Life are based on European datasets. The recycling processes in the End-of-Life are based on European and Global datasets.

#### Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Unbekannt

## LCA: Scenarios and additional technical information

Additional technical information for the declared module.

#### Transport to the building site (A4)

Name	Value	Unit
Litres of fuel truck (per piece)	0.006	l/100km
Transport distance (truck)	10 - 5000	km
Transport distance (ship)	0 - 23000	km
Average transport distance (truck)	1300	km
Capacity utilisation (including empty runs)	85	%
Average transport distance (ship)	11300	km

In order to represent dormakaba's global distribution network, a sales-weighted average is used to model transport to the building site. The table for Module A4 shows both weighted average transportation distance (given regional concealed closer sales), which is used in the analysis, along with the variation in that distance.

#### Installation into the building (A5)

Name	Value	Unit
Output substances following waste treatment on site (packaging)	0.12	kg

#### Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

In case a **reference service life** according to applicable ISO standards is declared then the assumptions and in-use conditions underlying the determined RSL shall be declared. In addition, it shall be stated that the RSL applies to the reference conditions only.

The same holds for a service life declared by the manufacturer. Corresponding information related to in-use conditions needs not be provided if a service life taken from the list of service life by *BNB* is declared.

#### Reference service life

Name	Value	Unit
Life Span according to the manufacturer	20	a

#### End of life (C1-C4)

Name	Value	Unit
Recycling	2.9	kg

#### Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Recycling	100	%

Collection rate is 100%.

## LCA: Results

The table below summarizes which modules are declared (as indicated by an "X"), and which are not declared (as indicated with "MND").

**DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED; MNR = MODULE NOT RELEVANT)**

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	MND	MND	MND	MND	X	MND	X

### RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A1: 1 closer (2.9kg)

Parameter	Unit	A1-A3	A4	A5	C3	D
Global warming potential (GWP)	kg CO <sub>2</sub> eq	16.3	0.66	0.17	0.161	-10.3
Depletion potential of the stratospheric ozone layer (ODP)	kg CFC11 eq	1.91E-12	5.25E-17	4.09E-17	1.49E-16	7.79E-14
Acidification potential of land and water (AP)	kg SO <sub>2</sub> eq	6.48E-02	1.54E-02	3.56E-05	5.21E-05	-4.35E-02
Eutrophication potential (EP)	kg PO <sub>4</sub> <sup>3</sup> eq	4.61E-03	1.74E-03	6.71E-06	9.62E-06	-2.75E-03
Formation potential of tropospheric ozone photochemical oxidants (POCP)	kg Ethen eq	5.55E-03	4.91E-04	2.35E-06	3.07E-06	-3.1E-03
Abiotic depletion potential for non fossil resources (ADPE)	kg Sb eq	9.34E-04	2.18E-08	3.34E-09	2.38E-08	-3.53E-04
Abiotic depletion potential for fossil resources (ADPF)	MJ	194	8.62	0.0471	0.0989	-103

### RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A1: 1 closer (2.9kg)

Parameter	Unit	A1-A3	A4	A5	C3	D
Renewable primary energy as energy carrier (PERE)	MJ	55.2	0.0318	1.809	0.0259	-34.9
Renewable primary energy resources as material utilization (PERM)	MJ	1.8	0	-1.8	0	0
Total use of renewable primary energy resources (PERT)	MJ	57	0.0318	0.00943	0.0259	-34.9
Non renewable primary energy as energy carrier (PENRE)	MJ	212.37	0	0	1.741	0
Non renewable primary energy as material utilization (PENRM)	MJ	1.63	0	0	-1.63	0
Total use of non renewable primary energy resources (PENRT)	MJ	214	8.63	0.0552	0.111	-116
Use of secondary material (SM)	kg	1.11	0	0	0	0
Use of renewable secondary fuels (RSF)	MJ	0	0	0	0	0
Use of non renewable secondary fuels (NRSF)	MJ	0	0	0	0	0
Use of net fresh water (FW)	m <sup>3</sup>	0.142	0.000147	0.000497	0.00068	-0.102

### RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A1: 1 closer (2.9kg)

Parameter	Unit	A1-A3	A4	A5	C3	D
Hazardous waste disposed (HWD)	kg	6.62E-06	1.12E-09	1.07E-10	9.35E-10	-3E-07
Non hazardous waste disposed (NHWD)	kg	2.68E+00	6.57E-05	5.34E-03	1.72E-02	-1.8E+00
Radioactive waste disposed (RWD)	kg	7.75E-03	3.02E-06	3.2E-06	4.6E-06	-5.22E-03
Components for re-use (CRU)	kg	0	0	0	0	0
Materials for recycling (MFR)	kg	0	0	0	2.73	0
Materials for energy recovery (MER)	kg	0	0	0	0	0
Exported electrical energy (EEE)	MJ	0	0	0.257	0.222	0
Exported thermal energy (EET)	MJ	0	0	0.467	0.513	0

## References

### ANSI A156.4

ANSI/BHMA A156.4 - 2013, Door controls - Closers

**Candidate List** of REACH Regulation /1907/2006/EC (date: 16.01.2020)

### ECHA

European Chemicals Agency

### EN 1154

EN 1154:2003, Building hardware - Controlled door closing devices

### EN 15804

EN 15804:2012-04

Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products

### GaBi ts

thinkstep AG, GaBi Software System and Database for Life Cycle Engineering (SP39). 1992-2019  
Copyright thinkstep AG

### ISO 9001

Quality Management System - ISO 9001:2015

**ISO 14001**

Environmental Management System: ISO 14001:2015

**ISO 14040**

EN ISO 14040:2006, Environmental management - Life cycle assessment - Principles and framework

**ISO 14044**

EN ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines

**ISO 50001**

Energy Management System: ISO 50001:2011

**PCR Part A**

Institut Bauen und Umwelt e.V., Product Category Rules for Construction Products from the range of Environmental Product

Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report

**PCR Part B**

PCR Guidance-Texts for Building-Related Products and Services. From the range of Environmental Product Declarations of Institute Construction and Environment e.V. (IBU). Part B: Requirements on the EPD for building hardware products

**REACH**

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Regulation (EC) No 1907/2006  
The literature referred to in the Environmental Product Declaration must be listed in full. Standards already fully quoted in the EPD do not need to be listed here again.  
The current version of PCR Part A and PCR Part B of the PCR document on which they are based must be referenced.





**Publisher**

Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

+49 (0)30 3087748- 0  
[info@ibu-epd.com](mailto:info@ibu-epd.com)  
[www.ibu-epd.com](http://www.ibu-epd.com)

---



**Programme holder**

Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

+49 (0)30 3087748- 0  
[info@ibu-epd.com](mailto:info@ibu-epd.com)  
[www.ibu-epd.com](http://www.ibu-epd.com)

---



**Author of the Life Cycle Assessment**

Sphera Solutions GmbH  
Hauptstraße 111- 113  
70771 Leinfelden-Echterdingen  
Germany

+49 711 341817-0  
[info@sphera.com](mailto:info@sphera.com)  
[www.sphera.com](http://www.sphera.com)

---



**Owner of the Declaration**

dormakaba International Holding GmbH  
DORMA Platz 1  
58256 Ennepetal  
Germany

+49 2333 793-0  
[info.de@dormakaba.com](mailto:info.de@dormakaba.com)  
[www.dormakaba.com](http://www.dormakaba.com)