

ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025 and EN 15804+A2 

Triflex GmbH & Co. KG
Triflex Finish 205



Triflex

Owner of the declaration

Triflex GmbH & Co. KG
Karlstraße 59
32423 Minden
Germany

Product

Triflex Finish 205

Declared product / Declared unit

1 kg of applied resin

**This declaration is based on Product
Category Rules**

EN 15804:2012 + A2:2019,
NPCR Part A:2021 ,
IBU PCR Part B: Requirements on the EPD
for Reaction Resin Products ,
EN 16757:2022

Program operator:

EPD Global
Majorstuen P.O. Box 5250
N-0303 Oslo
Norway

Declaration number

NEPD-10972-10972-2

Registration number

NEPD-10972-10972-2

Issue date

12.02.2026

Valid to

11.02.2031

EPD Software

Emidat Platform v1.0.0

General Information

Product

Triflex Finish 205

Program Operator

EPD Global
Majorstuen P.O. Box 5250
N-0303 Oslo
Norway
Phone: +47 23 08 80 00
Email: post@epd-norge.no

Declaration Number

NEPD-10972-10972-2

This declaration is based on Product Category Rules

EN 15804:2012 + A2:2019,
NPCR Part A:2021 ,
IBU PCR Part B: Requirements on the EPD for Reaction
Resin Products ,
EN 16757:2022

Statements

The owner of the declaration shall be liable for the underlying information and evidence. The Norwegian EPD Foundation shall not be liable with respect to manufacturer, life cycle assessment data and evidences.

Declared unit

1 kg of applied resin with a reference service life of 25 years

General information on verification of EPD from EPD tools

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD Global, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD Global's General Programme Instructions for further information on EPD tools.

Verification of EPD tool

Charlotte Merlin, FORCE Technology
(no signature required)

Owner of the declaration

Triflex GmbH & Co. KG

Contact person

triflex@emidat.com

Phone

+49 571 38780627

Email

triflex@emidat.com

Manufacturer

Triflex GmbH & Co. KG
Karlstraße 59
32423 Minden, Germany

Place of production

Minden, Germany

Management system

ISO 14001 , ISO 50001 , ISO 9001

Issue date

12.02.2026

Valid to

11.02.2031

Year of study

2023

Comparability

EPDs of construction products may not be comparable if they do not comply with EN 15804 and are not seen in a building context. EPD data may not be comparable if the datasets used are not developed in accordance with EN 15804 and if the background systems are not based on the same database (including primary and secondary data).

Development and verification of EPD

The declaration was created using the Emidat EPD tool v1.0, developed by Emidat GmbH. The EPD tool has been approved by EPD Global.

Developer of EPD: Besnik Hasani

Reviewer of company-specific input data and EPD: Dr. Arne Hägerbäumer

Approved




Håkon Hauan, The Norwegian EPD Foundation

Product

Product description

Triflex Cryl Finish 205 is a 2-component pigmented finish with a polymethyl methacrylate resin (PMMA) base. Triflex Cryl Finish 205 is fast curing, rapidly resistant, satin gloss, UV-resistant and solvent-free according to DIRECTIVE 2004/42/EC.



Triflex Cryl Finish 205 is used as a finish on dressed and undressed Triflex PMMA systems to increase chemical and mechanical resistance.

Product specification

Name of ingredient	Share of total weight	Country of origin
Additives	0 - 2 %	Various
Admixtures	2 - 10 %	Various
Aggregates	0 - 2 %	Germany
Chemicals	25 - 50 %	Various
Gypsum	0 - 2 %	Germany
Pigments	2 - 10 %	Germany
Plastics	10 - 25 %	Various
Polymers	25 - 50 %	Various
Resins	2 - 10 %	Belgium
Supplementary cementitious materials	0 - 2 %	Germany

Technical data

	Unit	Value
Gross density	kg / m ³	1050
Productiveness	kg / m ²	0.6

Market

Germany

Recipients

B2B

LCA: Calculation rules

Declared unit


1 kg of applied resin

Reference service life

25 years

This value represents a conventional reference lifespan, not a guaranteed performance duration, and assumes normal exposure conditions, adequate design, and routine maintenance.

System boundary



Data quality

The foreground data are based on extensive and detailed data collection at the production site of the manufacturer, covering key processes such as raw material sourcing, formulation, and manufacturing. These foreground data are fully linked with corresponding datasets from the background database (ecoinvent 3.10) or with EN15804+A2-compliant EPDs, ensuring consistency, reliability, and maintaining alignment with the latest industry standards.

The overall data representativeness is rated as good with an overall score of 4.00/5, in accordance with EN 15804+A2 Annex E guidance on data quality assessment, considering geographical, technical, and temporal representativeness.

The following discloses all processes or activities assessed with very poor or poor data representativeness according to EN 15804+A2, as well as those assessed as fair that contribute more than 30 % to any core impact indicator in A1–A3:

Element	Contribution	Indicator	Minimal Representativeness	Source	Year
Chemicals	60.2%	ODP	Poor	Ecoinvent 3.10	2023
Chemicals	47.4%	EP-marine	Fair	Ecoinvent 3.10	2023
Polymers	36.8%	AP	Poor	Ecoinvent 3.10	2023
Plastics	23.3%	ADPE	Poor	Ecoinvent 3.10	2023

Element	Contribution	Indicator	Minimal Representativeness	Source	Year
Admixtures	8.6%	ADPE	Poor	Ecoinvent 3.10	2023
Plastics	4.1%	ADPE	Poor	Ecoinvent 3.10	2023
Additives	1.4%	WDP	Poor	Ecoinvent 3.10	2023
Admixtures	1.0%	ADPE	Poor	Ecoinvent 3.10	2023
Gypsum	0.9%	ADPE	Poor	Ecoinvent 3.10	2023
Chemicals	0.8%	ADPE	Very poor	Ecoinvent 3.10	2023
Admixtures	0.7%	ADPE	Very poor	Ecoinvent 3.10	2023
Additives	0.2%	ADPE	Very poor	Ecoinvent 3.10	2023
Pigments	0.2%	ADPE	Very poor	Ecoinvent 3.10	2023
Admixtures	0.2%	ADPE	Poor	Ecoinvent 3.10	2023
Pigments	0.0%	EP-terrestrial	Poor	Ecoinvent 3.10	2023
Supplementary cementitious materials	0.0%	ADPE	Poor	Ecoinvent 3.10	2023

System boundaries (X=included, MND=module not declared)

	Production			Installation		Use stage							End-of-Life				Next product system
	Raw material supply	Transport	Manufacturing	Transport	Installation Process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational Energy Use	Operational Water Use	Demolition	Transport	Waste Processing	Disposal	Benefits and loads beyond the system boundary
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	x	x	x	x	x	MND	MND	MND	MND	MND	MND	MND	x	x	x	x	x
Geography			DE	DE	DE	MND	MND	MND	MND	MND	MND	MND	DE	DE	DE	DE	DE

For the geographies modeled in A1 and A2, refer to *Product specification*.

Type of EPD: Cradle to gate with options, modules A4-5, C1-C4, and D

Stage of Material Production and Construction

Module A1: Extraction and processing of reaction resin raw materials

Module A2: Transportation of raw material to the reaction resin plant

Module A3: Reaction resin production at the plant and waste treatment

Module A4: Transportation to the construction site

Module A5: Includes all processes associated with the reaction resin installation, as well as the production, transportation, and treatment of unused reaction resin

Disposal Stage

Module C1: Demolition/Dismantling of the building

Module C2: Transportation of mixed construction waste for processing

Module C3: Recycling of reaction resin waste as part of its carrier material. No separation of the reaction resin waste from the carrier material is possible. Concrete is used as the carrier material

Module C4: Final disposal of reaction resin waste in sanitary landfill together with carrier material. No separation of the reaction resin waste from the carrier material is possible. Concrete is used as the carrier material

Credits and burdens outside the system boundaries

Module D: Credits and burdens for the use of production waste in A3 or packaging waste in A5 as a secondary fuel or thermal/electrical energy generation. There are no credits and burdens from the EoL treatment of the reaction resin waste, as it cannot be separated from its carrier material. Concrete is used as the carrier material

Cut-off criteria

No cut-offs were applied.

Allocation

Foreground inventory data (energy and fuels, ancillary materials, emissions and waste) was collected at the production-process level. Using the total output of the production process in 2023, these flows are allocated to the reference product based on mass.

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport to the building site (A4)	Value	Unit
Transported mass: Product and packaging	1.02	kg
Truck: Distance	300.00	km
Truck: Energy demand	1.58	MJ / t*km
Truck: Activity	transport, freight, lorry >32 metric ton, EURO6	-
Truck: Capacity utilization	53.30	%

Installation into the building (A5)	Value	Unit
Treatment of packaging waste	Incineration	
Installation loss	1.00	%
NMVO emissions during curing	0.03	kg

Demolition (C1)	Value	Unit
Amount of energy spent by building machines in demolition (Bozdag, 2007)	0.01	kWh / kg

Transport to the waste facility (C2)	Value	Unit
Mass to landfill	0.30	kg
Mass to recycling	0.70	kg
Distance to recycling	50.00	km
Distance to landfill	50.00	km
Truck: Activity	transport, freight, lorry >32 metric ton, EURO6	-
Truck: Capacity utilization	53.30	%
Truck: Distance	50.00	km
Truck: Energy demand	1.58	MJ / t*km

Waste processing (C3)	Value	Unit
Material for recycling	0.70	kg
Recycling rate	70.00	%

Disposal (C4)	Value	Unit
Material for landfill	0.30	kg

Reuse, recovery and/or recycling potentials (D)	Value	Unit
Substitution of electrical energy production	0.02	MJ
Substitution of thermal energy production	0.22	MJ

Calculation of benefits and loads per EN 15804+A2.

LCA: Results

The following results are based on the market-based electricity approach applied to the foreground system (A3). Further details on electricity data are provided in the Additional Requirements section.

Core environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO ₂ -eq.	5.67e+00	3.16e-02	8.15e-02	3.61e-03	5.18e-03	6.20e-03	2.69e-03	-1.89e-02
GWP-fossil	kg CO ₂ -eq.	5.65e+00	3.16e-02	8.13e-02	3.61e-03	5.18e-03	4.29e-03	1.88e-03	-1.87e-02
GWP-biogenic	kg CO ₂ -eq.	1.67e-02	1.59e-05	1.95e-04	3.60e-07	2.60e-06	1.91e-03	8.17e-04	-2.14e-04
GWP-luluc	kg CO ₂ -eq.	2.94e-03	1.12e-05	3.35e-05	3.13e-07	1.84e-06	3.73e-07	9.74e-07	-5.14e-06
ODP	kg CFC-11-Eq	1.17e-07	6.59e-10	1.42e-09	5.52e-11	1.08e-10	6.57e-11	5.42e-11	-7.44e-10
AP	mol H ⁺ -Eq	3.14e-02	7.47e-05	3.43e-04	3.25e-05	1.22e-05	3.87e-05	1.33e-05	-1.54e-05
EP-freshwater	kg P-Eq	6.48e-04	2.22e-06	1.37e-05	1.05e-07	3.64e-07	1.25e-07	1.56e-07	-2.85e-06
EP-marine	kg N-Eq	5.02e-03	1.96e-05	5.75e-05	1.51e-05	3.21e-06	1.80e-05	5.06e-06	-5.50e-06
EP-terrestrial	mol N-Eq	4.27e-02	2.12e-04	4.97e-04	1.65e-04	3.47e-05	1.97e-04	5.53e-05	-5.31e-05
POCP	kg NMVOC-Eq	2.32e-02	1.30e-04	2.88e-02	4.93e-05	2.12e-05	5.87e-05	1.98e-05	-3.26e-05
ADPE	kg Sb-Eq	1.54e-05	9.03e-08	2.26e-07	1.29e-09	1.48e-08	1.54e-09	2.98e-09	-9.24e-09
ADPF	MJ, net calorific value	9.98e+01	4.75e-01	1.12e+00	4.72e-02	7.77e-02	5.61e-02	4.60e-02	-2.97e-01
WDP	m ³ world Eq deprived	1.29e+00	2.38e-03	1.44e-02	1.15e-04	3.90e-04	1.37e-04	1.29e-04	-7.26e-04

GWP-total: Global Warming Potential - total **GWP-fossil:** Global warming potential - fossil **GWP-biogenic:** Global Warming Potential - biogenic **GWP-luluc:** Global Warming Potential - luluc **ODP:** Depletion potential of the stratospheric ozone layer **AP:** Acidification potential, Accumulated Exceedance **EP-freshwater:** Eutrophication potential - freshwater **EP-marine:** Eutrophication potential - marine **EP-terrestrial:** Eutrophication potential - terrestrial **POCP:** Photochemical Ozone Creation Potential **ADPE:** Abiotic depletion potential - non-fossil resources **ADPF:** Abiotic depletion potential - fossil resources **WDP:** Water (user) deprivation potential

Additional indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	disease incidence	2.92e-07	3.08e-09	3.31e-09	9.25e-10	5.04e-10	6.31e-09	3.02e-10	-9.32e-11
IRP	kBq U235-Eq	1.14e-01	5.77e-04	1.74e-03	2.11e-05	9.44e-05	2.51e-05	2.93e-05	-5.63e-04
ETP-fw	CTUe	3.24e+01	1.12e-01	9.38e-01	6.68e-03	1.84e-02	7.95e-03	6.29e-03	-2.02e-02
HTP-c	CTUh	1.85e-08	2.02e-10	2.39e-10	1.41e-11	3.31e-11	1.68e-11	8.48e-12	-2.92e-11
HTP-nc	CTUh	2.23e-07	3.13e-10	4.09e-09	6.40e-12	5.13e-11	7.62e-12	8.26e-12	-3.31e-11
SQP	dimensionless	6.68e+00	4.77e-01	9.83e-02	3.30e-03	7.82e-02	3.93e-03	9.05e-02	-8.51e-03

PM: Potential incidence of disease due to PM emissions **IRP:** Potential Human exposure efficiency relative to U235 **ETP-fw:** Potential Comparative Toxic Unit for ecosystems **HTP-c:** Potential Comparative Toxic Unit for humans - cancer effects **HTP-nc:** Potential Comparative Toxic Unit for humans - non-cancer effects **SQP:** Potential Soil quality index

IRP: This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

ETP-fw, HTP-c, HTP-nc and SQP: The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experienced with these indicators.

Use of resources

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	1.91e+00	7.53e-03	2.59e-02	2.89e-04	1.23e-03	3.43e-04	4.26e-04	-8.49e-03
PERM	MJ	1.62e-02	0.00e+00	1.62e-04	0.00e+00	0.00e+00	-1.14e-02	0.00e+00	0.00e+00
PERT	MJ	1.93e+00	7.53e-03	2.61e-02	2.89e-04	1.23e-03	-1.10e-02	4.26e-04	-8.49e-03
PENRE	MJ	7.55e+01	4.75e-01	8.81e-01	4.72e-02	7.77e-02	5.61e-02	4.60e-02	-2.97e-01
PENRM	MJ	2.43e+01	0.00e+00	2.43e-01	0.00e+00	0.00e+00	-1.70e+01	0.00e+00	0.00e+00
PENRT	MJ	9.98e+01	4.75e-01	1.12e+00	4.72e-02	7.77e-02	-1.69e+01	4.60e-02	-2.97e-01
SM	kg	5.87e-03	0.00e+00	5.87e-05	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
RSF	MJ	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
NRSF	MJ	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
FW	m ³	3.30e-02	6.90e-05	3.77e-04	3.06e-06	1.13e-05	3.65e-06	4.77e-05	-2.27e-05

PERE: Primary energy resources - renewable: use as energy carrier **PERM:** Primary energy resources - renewable: used as raw materials **PERT:** Primary energy resources - renewable: total **PENRE:** Primary energy resources - non-renewable: use as energy carrier **PENRM:** Primary energy resources - non-renewable: used as raw materials **PENRT:** Primary energy resources - non-renewable: total **SM:** Use of secondary material **RSF:** Renewable secondary fuels **NRSF:** Non-renewable secondary fuels **FW:** Net use of fresh water

Waste flows

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	2.70e-03	0.00e+00	2.70e-05	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
NHWD	kg	0.00e+00	0.00e+00	2.76e-02	0.00e+00	0.00e+00	0.00e+00	3.00e-01	0.00e+00
RWD	kg	0.00e+00							

HWD: Hazardous waste disposed **NHWD:** Non hazardous waste disposed **RWD:** Radioactive waste disposed

Output flows

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
CRU	kg	0.00e+00							
MFR	kg	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00	7.00e-01	0.00e+00	0.00e+00
MER	kg	0.00e+00							
EEE	MJ	3.43e-03	0.00e+00	1.27e-02	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00
EET	MJ	4.62e-02	0.00e+00	1.72e-01	0.00e+00	0.00e+00	0.00e+00	0.00e+00	0.00e+00

CRU: Components for re-use **MFR:** Materials for recycling **MER:** Materials for energy recovery **EEE:** Exported electrical energy **EET:** Exported thermal energy

Name	Value	Unit
Biogenic carbon content in product	7.42e-04	kg C
Biogenic carbon content in accompanying packaging	0.00e+00	kg C

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

Electricity consumption in the manufacturing phase is composed from the source below. This EPD follows the market-based approach.

Electricity	Quantity [kWh]	Emission Factor [kg CO ₂ e/kWh]
electricity production, hydro, pumped storage (DE)	0.05	0.72

Dangerous substances

The product contains no hazardous substances given by the REACH Candidate List or the Norwegian Priority List.

Additional environmental information

Additional environmental impact indicators required in NPCR Part A for construction products

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-IOBC	kg CO ₂ -eq.	5.66e+00	3.16e-02	8.14e-02	3.61e-03	5.18e-03	4.29e-03	1.88e-03	-1.87e-02

GWP-IOBC: Global Warming Potential - Instantaneous oxidation of biogenic carbon

Bibliography

CEN/TR 15941:2010	Sustainability of construction works - Environmental product declarations - Methodology for selection and use of generic data
EN 15804:2012+A2:2019	Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products
EN 15942:2022-04	Sustainability of construction works - Environmental product declarations - Communication format business-to-business
ISO 14025:2011-10	Environmental labels and declarations - Type III environmental declarations - Principles and procedures
ISO 14040:2021-02	Environmental management - Life cycle assessment - Principles and framework
ISO 14044:2021-02	Environmental management - Life cycle assessment - Requirements and guidelines
EF 3.1	Environmental Footprint (EF) Life Cycle Impact Assessment method - Characterisation Factors version 3.1, European Commission, Joint Research Centre (JRC)
ecoinvent 3.10	ecoinvent, Zurich, Switzerland, database version 3.10
NPCR Part A:2021	Construction products and services, Version 2.0. Issue date: 24.03.2021; validity extended to 24.03.2026.
IBU	Part B: Requirements on the EPD for Reaction resin products, 2024, Version 7. Issue date: 01.08.2024.
EN 16757:2022	Sustainability of construction works – Environmental product declarations – Product category rules for concrete and concrete elements.
Kaethner, S. C. & BurrIDGE, J. A., 2012	Embodied CO2 of structural frames, The Structural Engineer, 8.

 Powered by EPD-Norway	Program Operator	Phone	+47 23 08 80 00
	EPD Global P.O. Box 5250 Majorstuen, N-0303 Oslo Norway	Email	post@epd-norge.no
 Powered by EPD-Norway	Publisher	Web	www.epd-global.no
	EPD Global P.O. Box 5250 Majorstuen, N-0303 Oslo Norway	Phone	+47 23 08 80 00
	Owner of the declaration	Email	triflex@emidat.com
	Triflex GmbH & Co. KG Karlstraße 59, 32423 Minden Germany	Web	none
	Author of the life cycle assessment	Phone	+49 571 38780627
	Triflex GmbH & Co. KG Karlstraße 59, 32423 Minden Germany	Email	triflex@emidat.com
	ECO Platform	Web	www.eco-platform.org
	ECO Portal	Web	ECO Portal
	Developer of EPD generator	Phone	+49 176 56 96 77 91
	Emidat GmbH Sandstraße 33, 80335 München Germany	Email	epd@emidat.com
		Web	www.emidat.com