

EXCELLENCE Genius

ACCZENT EXCELLENCE GENIUS 70

TAPIFLEX EXCELLENCE GENIUS 70

EN 651	-	
ISO 10582		-
EN ISO 10874	34-43	34
EN 651	-	
EN ISO 10582		-
EN ISO 24346	2.45 mm	3.50 mm
EN ISO 23997	3400 g/m ²	3680 g/m ²
EN ISO 24340	0.70 mm	0.70 mm
EN ISO 24341		
EN 14041	0120-092-DoP-2019-12	0120-093-DoP-2019-12
EN ISO 13501-1		
EN 1815	≤ 2.0 kV	≤ 2.0 kV
EN ISO 10456	0.02 m ² K/W	0.04 m ² K/W
EN 13893	≥ 0.3	≥ 0.3
EN ISO 24343-1		
NF EN ISO 717 / 2	ΔLw = 4 dB	ΔLw = 19 dB
NF S31-074	L _{n,e,w} < 85 dB -	L _{n,e,w} < 65 dB -
DIN 51130	R9/R10	R9/R10
EN 424		
ISO 4918		
EN ISO 23999	≤ [2] mm	≤ [3] mm
EN ISO 105-B02	≥ 6	≥ 6
EN ISO 23999		
EN ISO 26987		
EN 16516	≤ 10 µg/m ³	≤ 10 µg/m ³
25		25

																
005	1287 707	S 3010-Y20R	108	1287 716	S 2502-Y	185	1287 019	S 3040-B40G	500	1287 524	S 3500-N	509	1287 546	S 6005-Y50R		
010	1287 777	S 3020-Y20R	110	1287 530	S 3005-Y50R	186	1287 598	S 2050-G80Y	501	1287 585	S 6502-Y	510	1287 503	S 6020-Y60R		
014	1287 832	S 6000-N	128	1287 572	S 3005-Y20R	200	1287 174	S 3010-Y20R	502	1287 572	S 2502-Y	932	1287 188	S 2020-B50G		
104	1292 770	S 2502-Y	130	1291 817	S 3010-B10G	401	1291 214	S 3005-G80Y	503	1287 713	S 3005-Y20R	935	1287 201	S 5020-B30G		
107	1292 450	S 6005-R80B	131	1287 639	S 2020-G90Y	402	1287 848	S 3005-Y20R	508	1294 727	S 5502-R	942	1287 517	S 3040-Y70R		