

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

JACKOBOARD



BEWI

Owner of the declaration:

BEWI ASA, Insulation and Construction

Product:

JACKOBOARD

Declared unit:

1 m²

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR.

NPCR 012:2022 Part B for Thermal insulation products

Program operator:

EPD-Global

Declaration number:

NEPD-15739-19709

Issue date:

28.05.2026

Valid to:

28.05.2031

EPD software:

LCAno EPD generator ID: 1538592

General information

Product

JACKOBOARD

Program operator:

EPD-Global
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-global.com

Declaration number:

NEPD-15739-19709

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR.
NPCR 012:2022 Part B for Thermal insulation products

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD-Global shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

1 m² JACKOBOARD

Declared unit with option:

A1, A2, A3, A4, A5, C1, C2, C3, C4, D

Functional unit:

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Global, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Global's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPD-Global's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

Owner of the declaration:

BEWI ASA, Insulation and Construction
Contact person: Marc Storm Andersen
Phone: +45 72157902
e-mail: marc.andersen@bewi.com

Manufacturer:

BEWI Insulation Germany and Belgium
Europe

Place of production:

JACKON Insulation GmbH
Ritzlebener Str.1
39619 Arendsee, Germany

Management system:

ISO 14001 og 9001 for all production sites

Organisation no:

925437948

Issue date:

28.05.2026

Valid to:

28.05.2031

Year of study:

2025

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804:2012+A2:2019 and seen in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD-Global. NEPDT97

Developer of EPD: Mark Plate

Reviewer of company-specific input data and EPD: Mikael Danestedt

Approved:



Håkon Hauan, CEO EPD-Global

Product

Product description:

JACKOBOARD® construction boards are made of extruded polystyrene foam (JACKODUR®KF), with a coating of special mortar and glass fibre fabric on both sides. JACKODUR®KF is a polystyrene insulation foam material that complies with EN 13164, which is produced in the form of boards with a mean gross density of 33 kg/m³. The calculated density of the construction board, including the coating, is 186 kg/m³. The construction boards are supplied with smooth edges. Use of the product is subject to the relevant national regulations in the country of installation. In Germany, for example, this includes the building regulations of the individual federal states and the technical regulations derived from them.

This LCA is based on the Jackoboard F 20mm tickness, but can also be used for other ticknesses with the conversion factor found under System boundaries.

Product specification

Materials	kg	%
Cement	3.02	95.66
Flame retardant	0.006	0.1899
JACKODUR®KF (without FR)	0.017	0.5381
Reinforcement	0.114	3.61
Total	3.16	100.00

Packaging	kg	%
Packaging - Plastic	0.011	2.74
Packaging - Wood	0.391	97.26
Total incl. packaging	3.56	100.00

Technical data:

Name	Value	Unit	Norm
Gross density of the core material (polymer foam)	> 30	kg / m ³	EN 1602
Tensile strength	0,3	N/mm ²	EN 1607
Reaction to fire	E	class	EN 13501-1
Dimensional stability at 70°C and 90% relative humidity	< 5	%	EN 1605
Compressive stress at 10% deformation or compressive	200	kPa	EN 826
Deformation under 40 kPa load and 70°C	< 5	%	EN 1605

Market:

Europe

Reference service life, product

A reference service life (RSL) according to ISO 15686 cannot be declared. The durability of JACKOBOARD is normally at least as long as the lifetime of the building in which it is used (more than 80 years).

Reference service life, building or construction works

As in the construction where it is used.

LCA: Calculation rules

Declared unit:

1 m² JACKOBOARD

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

< 0,5%

Allocation:

The allocation is made in accordance with the provisions of EN 15804+A2. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:


Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Cement	ecoinvent 3.6	Database	2019
Expansion gas	ecoinvent 3.6	Database	2019
Expansion gas	ecoinvent 3.6	Database	2020
Filler	ecoinvent 3.6	Database	2019
Flame retardant	Ecoinvent 3.6	Database	2019
Packaging - EPS	Plastics Europe + ecoinvent 3.6	European average.	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Packaging - Wood	ecoinvent 3.6	Database	2019
Plastic - Polystyrene (PS)	Plastics Europe + ecoinvent 3.6	European average.	2020
Plastic - Recycled	Supplier	EPD	0
Reinforcement	ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage								End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use		De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7		C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND		X	X	X	X	X

System boundary:



Conversion factor GWP total						
A1-A3	6mm	12mm	20mm	30mm	50mm	80mm
JACKOBOARD F	0,731	0,754	1,00	1,252	1,821	2,565
A1-D	6mm	12mm	20mm	30mm	50mm	80mm
JACKOBOARD F	0,776	0,806	1,00	1,207	1,672	2,194

Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (kgkm)	36.7 %	628.00	0.043	l/tkm	27.00
Assembly (A5)	Unit	Value			
Waste, packaging, wood to average treatment - A5 (inkl transport) (kg)	kg	0.391			
Waste, packaging, plastic to average treatment - A5 (inkl transport) (kg)	kg	0.011			
De-construction demolition (C1)	Unit	Value			
Demolition of insulated concrete, C1 (kg)	kg	3.15			
Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 6 (kgkm)	53.3 %	20.00	0.023	l/tkm	0.46
Waste processing (C3)	Unit	Value			
Waste treatment of cement-based product after demolition, C3 (kg)	kg	3.15			
Disposal (C4)	Unit	Value			
Waste, inert waste, to landfill (kg)	kg	3.15			
Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of thermal energy (MJ)	MJ	4.11			
substitution of electricity (MJ)	MJ	0.2718			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact												
Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	GWP-total	kg CO ₂ -eq	1.54E+00	1.68E-01	1.33E-01	3.83E-01	1.14E-02	1.26E-02	6.50E-03	2.27E-03	2.59E-02	-2.47E-02
	GWP-fossil	kg CO ₂ -eq	2.13E+00	1.68E-01	1.33E-01	3.83E-01	1.14E-02	1.26E-02	6.50E-03	2.24E-03	2.59E-02	-2.39E-02
	GWP-biogenic	kg CO ₂ -eq	-5.87E-01	6.94E-05	5.93E-05	1.58E-04	5.13E-05	2.37E-06	2.78E-06	1.93E-05	3.02E-05	-4.92E-05
	GWP-luluc	kg CO ₂ -eq	1.14E-03	5.96E-05	1.47E-05	1.36E-04	2.77E-06	9.94E-07	1.98E-06	3.10E-06	6.36E-06	-8.22E-04
	ODP	kg CFC11-eq	1.06E-07	3.80E-08	1.75E-08	8.67E-08	1.73E-09	2.72E-09	1.57E-09	4.41E-10	9.79E-09	-1.74E-03
	AP	mol H ⁺ -eq	7.76E-03	4.82E-04	1.61E-04	1.10E-03	8.57E-05	1.32E-04	2.09E-05	1.81E-05	2.30E-04	-1.96E-04
	EP-FreshWater	kg P -eq	4.31E-05	1.34E-06	7.18E-07	3.06E-06	1.28E-07	4.59E-08	5.17E-08	1.41E-07	2.93E-07	-2.12E-06
	EP-Marine	kg N -eq	1.78E-03	9.53E-05	3.76E-05	2.18E-04	3.73E-05	5.83E-05	4.58E-06	5.31E-06	8.55E-05	-6.42E-05
	EP-Terrestrial	mol N -eq	1.99E-02	1.07E-03	4.12E-04	2.43E-03	3.93E-04	6.31E-04	5.11E-05	6.12E-05	9.43E-04	-6.95E-04
	POCP	kg NMVOC-eq	6.43E-03	4.08E-04	1.42E-04	9.32E-04	1.01E-04	1.76E-04	2.01E-05	1.64E-05	2.70E-04	-1.92E-04
	ADP-minerals&metals ¹	kg Sb-eq	3.09E-05	4.63E-06	1.09E-06	1.06E-05	1.75E-07	1.94E-08	1.16E-07	2.84E-08	2.33E-07	-2.37E-07
	ADP-fossil ¹	MJ	4.46E+01	2.53E+00	2.01E+00	5.79E+00	1.27E-01	1.74E-01	1.06E-01	6.95E-02	7.12E-01	-3.41E-01
	WDP ¹	m ³	1.39E+02	2.45E+00	6.34E-01	5.60E+00	2.03E-01	3.69E-02	8.09E-02	7.67E+00	4.39E+00	-4.25E+00

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

Additional environmental impact indicators

Indicator	Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
 PM	Disease incidence	7.50E-08	1.03E-08	9.63E-10	2.34E-08	1.05E-09	1.60E-08	5.97E-10	2.90E-10	4.91E-09	-1.19E-08
 IRP ²	kgBq U235 -eq	7.57E-02	1.11E-02	1.15E-03	2.53E-02	4.64E-04	7.57E-04	4.61E-04	1.17E-03	3.25E-03	-2.18E-03
 ETP-fw ¹	CTUe	1.70E+02	1.88E+00	5.20E-01	4.29E+00	1.44E-01	9.49E-02	7.72E-02	4.93E-02	3.88E-01	-1.86E+00
 HTP-c ¹	CTUh	1.16E-09	0.00E+00	4.00E-11	0.00E+00	1.60E-11	3.00E-12	0.00E+00	3.00E-12	1.60E-11	-3.40E-11
 HTP-nc ¹	CTUh	4.03E-08	2.05E-09	6.81E-10	4.69E-09	7.55E-10	8.80E-11	7.50E-11	4.40E-11	2.81E-10	-1.78E-09
 SQP ¹	dimensionless	7.47E+01	1.77E+00	2.45E-01	4.05E+00	7.56E-02	2.11E-02	1.21E-01	3.93E-02	2.74E+00	-2.28E+00

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9.0 E-03 = 9.0×10^{-3} = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use												
Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	PERE	MJ	8.58E+00	3.63E-02	1.11E+00	8.28E-02	2.63E-03	9.46E-04	1.33E-03	3.58E-02	2.55E-02	-2.11E+00
	PERM	MJ	5.43E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PERT	MJ	1.40E+01	3.63E-02	1.11E+00	8.28E-02	2.63E-03	9.46E-04	1.33E-03	3.58E-02	2.55E-02	-2.11E+00
	PENRE	MJ	3.09E+01	2.53E+00	2.01E+00	5.79E+00	1.27E-01	1.74E-01	1.06E-01	6.96E-02	7.12E-01	-3.41E-01
	PENRM	MJ	1.56E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PENRT	MJ	4.65E+01	2.53E+00	2.01E+00	5.79E+00	1.27E-01	1.74E-01	1.06E-01	6.96E-02	7.12E-01	-3.41E-01
	SM	kg	1.82E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	RSF	MJ	3.55E-02	1.30E-03	5.40E-04	2.96E-03	7.65E-05	0.00E+00	4.64E-05	0.00E+00	5.29E-04	-3.69E-04
	NRSF	MJ	1.05E-02	4.64E-03	4.65E-04	1.06E-02	8.50E-04	0.00E+00	1.56E-04	0.00E+00	1.14E-03	-1.25E-01
	FW	m ³	3.04E-02	2.71E-04	9.03E-04	6.19E-04	9.19E-05	8.94E-06	1.20E-05	1.19E-04	8.76E-04	-2.54E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9.0 E-03 = $9.0 \cdot 10^{-3}$ = 0.009"

End of life - Waste

Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	HWD	kg	6.69E-03	1.31E-04	1.97E-04	2.98E-04	0.00E+00	5.11E-06	5.77E-06	6.95E-06	0.00E+00	-1.60E-05
	NHWD	kg	2.68E-01	1.23E-01	1.02E-02	2.81E-01	4.02E-01	2.06E-04	9.17E-03	2.19E-04	3.15E+00	-8.06E-03
	RWD	kg	5.71E-05	1.73E-05	1.52E-06	3.94E-05	0.00E+00	1.21E-06	7.21E-07	7.35E-07	0.00E+00	-1.79E-06

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9.0 E-03 = 9.0×10^{-3} = 0.009"

End of life - Output flow

Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	CRU	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	MFR	kg	1.73E-02	0.00E+00	1.08E-02	0.00E+00	5.62E-03	0.00E+00	0.00E+00	3.15E+00	0.00E+00	0.00E+00
	MER	kg	3.81E-03	0.00E+00	2.52E-03	0.00E+00	3.91E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	EEE	MJ	5.87E-03	0.00E+00	3.76E-03	0.00E+00	2.72E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	EET	MJ	8.89E-02	0.00E+00	5.69E-02	0.00E+00	4.11E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9.0 E-03 = 9.0×10^{-3} = 0.009"

Biogenic Carbon Content

Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0.00E+00
Biogenic carbon content in accompanying packaging	kg C	1.62E-01

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, Germany (kWh)	ecoinvent 3.6	585.93	g CO ₂ -eq/kWh
Electricity, with Guarantee of origin, 01.01.2025 - 31.12.2025 - BEWI Arendsee, Germany (kWh)	ecoinvent 3.6	29.24	g CO ₂ -eq/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

JACKOBOARD® can be used indoor however they are generally not exposed to the indoor air but covered by a finishing element or system. The VOC emission testing meets the requirements of the AgBB/DIBt method. The tested products all comply with the requirements of DIBt and AgBB for the use in the indoor environment. The tested products also all achieved the A+ rating of the French VOC labelling scheme.

Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products											
Indicator	Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
GWPIOBC	kg CO ₂ -eq	1.54E+00	1.68E-01	1.30E-01	3.83E-01	1.14E-02	1.26E-02	6.50E-03	2.24E-03	2.59E-02	-2.44E-02

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21

Vold et. al., (2022) EPD generator for NPCR 012 Thermal insulation, Background information for EPD generator application and LCA data, LCA.no report number: 07.22.

NPCR Part A: Construction products and services. Ver. 2.0. April 2021, EPD-Norge.

NPCR 012 Part B for Part B for Thermal insulation products, Ver. 2.0, 31.03.2022, EPD Norway.

 epd-global Powered by EPD-Norway	Program operator and publisher EPD-Global Postboks 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-global.com
	Owner of the declaration: BEWI ASA, Insulation and Construction Hammarvikringen 64, HAMAR 7263, Norway	Phone: +45 72157902 e-mail: marc.andersen@bewi.com web: https://bewi.com
	Author of the Life Cycle Assessment LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	Developer of EPD generator LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	ECO Platform ECO Portal	web: www.eco-platform.org web: ECO Portal