

## **DECLARATION OF PERFORMANCE**

No.: Rigips\_Winkelprofil\_50\_30\_07\_LE\_2504

- (1) *Unique identification code of the product-type*  
**Rigips Winkelprofil 50/30-07**
- (2) *Intended use/es*  
**Metal framing component for gypsum plasterboard systems  
L/50/30 (EN 14195)**
- (3) *Manufacturer*  
**SAINT-GOBAIN RIGIPS GmbH  
Willstätterstraße 60  
D-40549 Düsseldorf**
- (4) *Authorised representative*  
**N/A**
- (5) *System/s of AVCP*  
**System 4**
- (6a) *Harmonised standard*  
**EN 14195:2005/AC:2006**
- Notified body/ies*  
**Internal**
- (6b) *European Assessment Document*  
**N/A**
- European Technical Assessment*  
**N/A**
- Technical Assessment Body*  
**N/A**
- Notified body/ies*  
**N/A**

(7) Declared performance/s

Essential characteristics	Performance
Reaction to fire (R2F) (for unprotected installation situations)	A1
Flexural strength Yield strength	240 N/mm <sup>2</sup>

(8) Appropriate Technical Documentation and/or Specific Technical Documentation  
N/A


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 03. April 2025



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

	
<b>SAINT-GOBAIN RIGIPS GmbH</b> Willstätterstraße 60 D-40549 Düsseldorf	
13	
<b>Rigips_Winkelprofil_50_30_07_LE_2504</b>	
<b>EN 14195:2005/AC:2006</b>	
<b>Metal framing component for gypsum plasterboard systems</b> <b>L/50/30 (EN 14195)</b> Notified body/ies: N/A	
Reaction to fire (R2F) (for unprotected installation situations)	A1
Flexural strength	240 N/mm <sup>2</sup>
Yield strength	240 N/mm <sup>2</sup>